

MC-10A & MC-11

Rugged, low-cost "MINI-CAT" Label Rewinders

Meet the popular MINI-CATs, the world's lowest-price Label Rewinders. They are capable of rewinding label rolls up to 4½ -inches wide (5-inches for MC-11), up to 8.6-inches (220-mm) in diameter at speeds up to 10-inches/second (25-cm/sec.) The MINI-CATs can also be used as Label Unwinders.


The MINI-CAT-10A (**MC-10A**) has a 3-inch diameter core holder. You can also use the included "coreless rewind" feature to rewind directly on-shaft. The MINI-CAT-11 (**MC-11**) includes a precision-crafted Adjustable Core Holder that adjusts in seconds to accept any core diameter from 1-inch to 4-inches (25- to 102-mm). The **MC-11** will also do coreless rewinding.

The MINI-CATs use LABELMATE's proprietary Constant Adjustable Torque™ ("CAT") technology to achieve reliable performance at an unprecedented low price. A special direct-drive motor, designed specifically for the MINI-CATs, offers bi-directional operation and trouble-free performance. No troublesome belts or clutches are used and no speed adjustments are required. Your MINI-CAT automatically adjusts to any printer speed up to 10-ips and even allows label back-feeding automatically if your printer requires it. A slide switch allows you to adjust the amount of rewind force.

The MINI-CATs have an inner label flange to keep the edge of the label web aligned as the labels are being rewound. Also available is an optional Adjustable Paper Guide (**APG-MC**) that mounts directly to the **MC-10A** or **MC-11** base plate and guides the outer edge of the labels. For the **MC-10A**, an optional plastic Outer Flange (**MC-10 Flange**) is also available. See photos below right.


Rugged steel construction allows your MINI-CAT to simply be set in place near your label printer. Special anti-slip feet keep the unit from moving.

Join thousands of others, and put a MINI-CAT to work for you today and enjoy the finest in low-cost label rewinding convenience and reliability.



MC-10A (above): You can use the included 3-inch core holder, or rewind "coreless" directly "on-shaft" without any label core!

MC-11 (below): Rewind on any core from 1-inch to 4-inches in diameter, or coreless.



MC-10A & MC-11 SPECIFICATIONS:

Label Width: **MC-10A** Up to 4.5" (114-mm). **MC-11** Up to 5" (125-mm).

Maximum Label Roll Weight: 8.5-lbs. (3.9-kg).

Label Roll Diameter: Up to 8.6" (220-mm).

Core Diameter: **MC-10A:** 3" (76-mm) or coreless. **MC-11:** Any from 1" to 4" (25- to 102-mm) or coreless.

Speed: Up to 10-ips (25+ cm/sec). Switch adjustable rewind force. No speed adjustments are required.

Start/Stop: Convenient ON-OFF switch. **Direction:** Bi-directional.

Power Requirements: 120vac 60Hz. 20 va. UL / CSA Listed Power Supply.


220-240 vac 50Hz units are available at the same price.

Size: H-W-D 9 x 6 x 11" (229 x 152 x 279-mm). **Weight:** 13-lbs. (5.9-kg).


Optional: Adjustable Paper Guide (**APG-MC**) Arm. For either the MC-10A or the MC-11.

Optional: Plastic Outer Flange (**MC-10 Flange**). For the MC-10A only.

Warranty: **3-Year Parts and Labor Limited Warranty**, the longest in the industry!
(One-year Limited Warranty on the included Power Supply Module.)



MC-11 with APG-MC



**MINI-CAT10A w/
optional Outer Flange**

The World's Leading Manufacturer of Label Dispensers, Rewinders, Unwinders, Slitters & Core Chucks

LABELMATE LLC, 12A Sunset Way, Henderson, NV 89014-2002 USA

Toll-Free in the USA! (877) 833-7149 (702) 435-8535 FAX (702) 435-8536

www.labelmate.com

E-mail: info@labelmate.com

LABELMATE EUROPE, 69 Avenue Alphonse XIII, B-1180 Brussels, BELGIUM +32 (2) 375-6960 FAX +32 (2) 375-3896