

Genie 2

Alphanumeric Pager



FEATURES

- :: Alphanumeric Display with 20 Characters per Line
- :: Easy to Read 2 Line English Language Display
- :: 6 Cap Code Addresses
- :: Button Activated Display Lighting
- :: Message Capacity of 65 Messages
- :: Up to 500 Characters per Message
- :: Practical Alarm Feature
- :: 4 Selectable Alert Tones plus Melody
- :: Urgent Feature with Priority Override
- :: Time and/or Date Stamp Added On Message Receipt
- :: Automatic Detection and Rejection of Duplicate Messages
- :: Windows PC Software Programmable or Exclusive Features Via Pager Buttons
- :: 700 Hours of Battery Life on a Single AAA Alkaline

SPECIFICATIONS

Addresses	6 Cap Codes
Selectable Languages	English
Dimensions (without holster)	76 (L) x 53 (W) x 17 (H) mm 3.0 (L) x 2.1 (W) x 0.7 (H) inches
Weight	65g / 2.3oz (including battery)
Battery	1 X AAA Alkaline
Approximate Battery Life	700 Hours
Frequencies Covered	135-175 MHz 278-287 MHz 406-478 MHz 925-932 MHz
Signal Transmission Type	POCSAG (CCIR)
Channel Spacing	20kHz / 25kHz
Data Transmission Rate	512bps, 1200bps or 2400bps
Modulation System	Carrier Frequency Shift Keying (NRZ)
Frequency Deviation	±4.5kHz
Receiving Sensitivity	512bps 5uV/m, 1200bps 7uV/m, 2400bps 9uV/m
Selectivity	65db ±25kHz
Spurious Rejection	60db+
Frequency Stability	10ppm (VHF), 5ppm (UHF), 3ppm (930 MHz)
Storage Temperature / Humidity	0°C/32F to 50°C/122F at 95% Humidity (Non-Condensing)

AUSTRALIA

PO Box 1037, OPDC
6916, PERTH, WA,

Ph: +61 8 6240 0000
Fax: +61 8 6240 0001

UNITED STATES

8301 Cypress Plaza Drive, Suite 105
JACKSONVILLE, FL, 32256-4416

Ph: +1 904 281 0073
Fax: +1 904 281 0074

